OEM Lithium Batterie Lifepo4 Home Battery Energizing Your Home With Flexible Energy Solutions

Basic Information

- Place of Origin:
- XWELL • Brand Name:
- Certification:
- UN38.3, MSDS, UL, CB, BIS, PSE, GB4943.1 safety standard, CE, FCC, ROHS, battery UN38.3, MSDS, UL, CB, BIS, PSE XW-HL1536 Model Number:

China

- Minimum Order Quantity: 1 pcs
- · Packaging Details: Carton
- Delivery Time:
- Payment Terms: L/C, D/A, D/P, T/T, Western Union,
- MoneyGram • Supply Ability: 5000 pcs per month

7-10 working days



Product Specification

 Sample Number: 	1、2、3、4 、5、6 Mdl
Competence:	5-30kwh
Power Cell Arrangement:	1-6s
Net Weight:	206.5kg
• Volt:	48V
 Ostensible Voltage: 	48V
Cell Battery Kind:	LiFePO4
 Rated Working Current: 	100A
Communication AC110V/220V/50Hz/60Hzr	CAN/RS485/RS232 nethod:
 Installation Method: 	Floor Installation
Highlight:	Flexible Energy Solutions Home Battery, Flexible Energy Solutions Lifepo4 Home Battery , Flexible Energy Solutions Lithium Batterie

OEM Lithium Batterie Lifepo4 Home Energy Storage System High-Voltage And Low-Voltage Stacking

Product Characteristics of Stackable Home Battery

The Stackable Home Battery is a revolutionary energy storage solution for your home. Designed to be stacked for increased capacity, it offers reliable and efficient power backup. With its advanced lithium-ion technology, it provides long-lasting performance and durability. Whether for power outages or to reduce your energy bills, the Stackable Home Battery is a smart investment for a sustainable future. Easily integrated into your home's electrical system, it gives you peace of mind and energy independence.

Available in many places Stackable Home Battery

Scope of application: household energystorage, communication base station, industrial energy storage mobile energy storage, field campingphotovoltaic energy storage, etc

Stackable Home Battery Specification

Model	1 Module	2 Modules	3 Modules	4 Modules	5 Modules	6 Modules		
Nominal capacity(kwh)	5.12	10.24	15.36	20.48	25.6	30.72		
Operating voltage	48V							
Weight (Kg)	96.5	151.5	206.5	261.5	316.5	371.5		
Nominal voltage	48V							
Dimension (mm)	600x460x 457	600x460x 637	600x460x 817	600x460x 997	600x460x 1177	600x460x 1357		
Battery cell type	LiFePO4							
Communication method	CAN/RS485/RS232							
Operating temperature range	Charging: 0~45 Discharging: -10~50							
Protection level	IP55							
Installation method	Floor installation							
Cycle life	>6000 Cycles(80%DOD)							
Peak charge/discharge current (@25 ,5S)	100A							
Self-discharge rate	≤3.5%/month/@25°C							
Parallel function	1S~6S							

Stackable Home Battery Connection Diagram



FAQ

- 1. Q: Are you a manufacturer?
- A: Yes, we have been offering specialized products in this field for 20 years.
- 2. Q: How do you pack these products?
- A: Usually packed according to export standard or your requirement.
- 3. Q: Is it customizable?
- A: Yes, according to your requirements.
- 4. Q: After-sales service
- A: 24-hour technical support by phone, email or skype
- 5. Q: What is your lead time?
- A: Spot goods usually take 3-5 days, and customization takes 5-7 days



XWELL GUANGDONG XWELL TECHNOLOGY CO., LTD.

+86 18620492985

Sales@esslithiumbattery.com

esslithiumbattery.com

Room 322, Building 3, No. 801, Qiaoxing Avenue, Xiaoluo Village, Shatou Street, Panyu District, Guangzhou, China