

Intelligent Modular Stackable Home Battery Reliable Energy Storage For **Sustainable Home Environments**

Basic Information

• Place of Origin: . Brand Name: XWELL

UN38.3,MSDS,UL,CB,BIS,PSE,GB4943.1 safety standard, CE, FCC, ROHS, battery UN38.3, MSDS, UL, CB, BIS, PSE Certification:

Model Number: XW-HL1536 • Minimum Order Quantity: 1 pcs Packaging Details: Carton

• Delivery Time: 7-10 working days

L/C, D/A, D/P, T/T, Western Union, • Payment Terms:

MoneyGram

5000 pcs per month Supply Ability:



Product Specification

 Pattern Number: 1、2、3、4、5、6 Mdl

5-30kwh • Capacity: • Electrochemical Cell 1-6s Arrangement:

Net Weight: 206.5kg Volt: 48V • Titled Voltageage: 48V Battery Cell Kind: LiFePO4 • Definedworking Current: 100A

 Communication CAN/F AC110V/220V/50Hz/60Hzmethod: CAN/RS485/RS232

Set Up Method: Floor Installation

Highlight: Intelligent Stackable Home Battery, Modular Stackable Home Battery

Sustainable Stackable Home Battery

more products please visit us on esslithiumbattery.com

Product Description

OEM Lithium Batterie Lifepo4 Home Energy Storage System High-Voltage And Low-Voltage Stacking

Product Characteristics of Stackable Home Battery

A Stackable Home Battery is an innovative and flexible energy storage solution designed specifically for residential applications.

This battery system features a modular and stackable design, allowing homeowners to easily customize their energy storage capacity according to their specific needs. Each individual battery module is compact and lightweight, making it convenient for installation and handling. They can be stacked vertically or horizontally, depending on the available space and the desired power output.









Scope of application: household energystorage, communication base station,industrial energy storage mobile energy storage, field campingphotovoltaic energy storage, etc

Stackable Home Battery Specification

| Model | 1 Modulo | 2 Madulas | 2 Madulas | 4 Madulas | 5 Modules | 6 Madulas |
|---|------------------------------------|-----------------|-----------------|-----------------|------------------|------------------|
| | | | | | | |
| Nominal capacity(kwh) | 5.12 | 10.24 | 15.36 | 20.48 | 25.6 | 30.72 |
| Operating voltage | 48V | | | | | |
| Weight (Kg) | 96.5 | 151.5 | 206.5 | 261.5 | 316.5 | 371.5 |
| Nominal voltage | 48V | | | | | |
| Dimension (mm) | 600x460x 457 | 600x460x 637 | 600x460x 817 | 600x460x 997 | 600x460x 1177 | 600x460x 1357 |
| Battery cell type | LiFePO4 | | | | | |
| Communication method | CAN/RS485/RS232 | | | | | |
| Operating temperature range | Charging: 0~45 Discharging: -10~50 | | | | | |
| Protection level | IP55 | | | | | |
| Installation method | Floor installation | | | | | |
| Cycle life | >6000 Cycles(80%DOD) | | | | | |
| Peak charge/discharge current (@25 ,5S) | 100A | | | | | |
| Self-discharge rate | ≤3.5%/month/@25°C | | | | | |
| Parallel function | 1S~6S | | | | | |

Stackable Home Battery Connection Diagram



FAQ

- Q: Are you a manufacturer?
 A: Yes, we have been offering specialized products in this field for 20 years.
 Q: How do you pack these products?
 A: Usually packed according to export standard or your requirement.
 Q: Is it customizable?

- A: Yes, according to your requirements.
 4. Q: After-sales service

- 4. 24-hour technical support by phone, email or skype 5. Q: What is your lead time? A: Spot goods usually take 3-5 days, and customization takes 5-7 days



XWELL GUANGDONG XWELL TECHNOLOGY CO., LTD.

+86 18620492985 Sales@esslithiumbattery.com
esslithiumbattery.com

Room 322, Building 3, No. 801, Qiaoxing Avenue, Xiaoluo Village, Shatou Street, Panyu District, Guangzhou, China